

dabmodel


User Manual

chacha

CC BY-NC-SA 4.0

Table of contents

1. Python project template	3
1.1 Features	3
2. Usage	4
2.1 Pulvinar dolor	4
2.2 Condimentum faucibus	4
2.3 Aliquam lacinia	4
3. Reference	5
3.1 Dabmodel	5



1. Python project template

A nice template to start blank python projects.

This template automate a lot of handy things and allow CI/CD automatic releases generation.

It is also collectings data to feed Jenkins build.

Checkout [Latest Documentation](#).

1.1 Features

1.1.1 Generic pipeline skeleton:

- Prepare
- GetCode
- BuildPackage
- Install
- CheckCode
- PlotMetrics
- RunUnitTests
- GenDOC
- PostRelease

1.1.2 CI/CD Environment

- Jenkins
- Gitea (with patch for dynamic Readme variables: <https://chacha.ddns.net/gitea/chacha/GiteaMarkupVariable>)
- Docker
- MkDocsWeb

1.1.3 CI/CD Helper libs

- VirtualEnv
- Changelog generation based on commits
- copier
- pylint + pylint_json2html
- mypy
- unittest + xmlrunner + junitparser + junit2htmlreport
- mkdocs

1.1.4 Python project

- Full .toml implementation
- .whl automatic generation
- dynamic versionning using git repository
- embedded unit-test

2. Usage

2.1 Pulvinar dolor

Donec dapibus est fermentum justo volutpat condimentum. Integer quis nunc neque. Donec dictum vehicula justo, in facilisis ex tincidunt in. Vivamus sollicitudin sem dui, id mollis orci facilisis ut. Proin sed pulvinar dolor. Donec volutpat commodo urna imperdiet pulvinar. Fusce eget aliquam risus. Vivamus viverra luctus ex, in finibus mi. Nullam elementum dapibus mollis. Ut suscipit volutpat ex, quis feugiat lacus consectetur eu.

2.2 Condimentum faucibus

Quisque auctor egestas sem, luctus suscipit ex maximus vitae. Duis facilisis augue et condimentum faucibus. Donec cursus, enim a sagittis egestas, lectus lorem eleifend libero, at tincidunt leo magna at libero. Nunc eros velit, suscipit luctus tempor vel, finibus et est. Curabitur efficitur pretium pulvinar. Donec urna lectus, vulputate quis turpis sed, placerat congue urna. Phasellus aliquet fermentum quam, non auctor elit porta nec. Morbi eu ligula at nisl ultricies condimentum vitae id ante.

2.3 Aliquam lacinia

In volutpat lorem ex, et fringilla nibh faucibus quis. Mauris et arcu elementum, auctor dui vitae, egestas arcu. Duis sit amet aliquam quam. Phasellus a odio turpis. Etiam tristique mi eu enim varius, eget facilisis est vestibulum. Aliquam lacinia nec purus sed luctus. Cras at laoreet erat.

3. Reference

3.1 Dabmodel

3.1.1 metadata

Metadata module module

Attributes

`__Name__` module-attribute

```
__Name__ = metadata['Name']
```

`__Summary__` module-attribute

```
__Summary__ = metadata['Summary']
```

`__version__` module-attribute

```
__version__ = version('dabmodel')
```

`dist` module-attribute

```
dist = distribution('dabmodel')
```

3.1.2 Appliance

Classes

Appliance

Bases: [IAppliance](#)

BaseFeature class Base class for Appliance. An appliance is a server configuration / image that is built using appliance's code and Fields.

Functions

validate_schema

```
validate_schema()
```

validate_schema_class classmethod

```
validate_schema_class()
```

3.1.3 Base element

Classes

BaseElement

Attributes

`__lam_class_mutable__` class-attribute instance-attribute

```
__lam_class_mutable__ = False
```

`__lam_initialized__` class-attribute instance-attribute

```
__lam_initialized__ = False
```

`__lam_object_mutable__` class-attribute instance-attribute

```
__lam_object_mutable__ = False
```

`__lam_options__` class-attribute instance-attribute

```
__lam_options__ = {}
```

```
def get_model_spec(self, name: str, module: str, memo: dict[str, Any]) -> ElementView: # memo[self.name] = {} init_fieldvalues = {} init_fielddtypes = {} for k, v in self.lam_schema.items(): if isinstance(v, LAMField_Element): memo[k] = {} init_fieldvalues[k] = v.value.get_model_spec(memo[k]) # clone = v.clone_unfrozen().value elif isinstance(v, LAMField): clone = deepcopy(v.value) init_fieldvalues[k] = clone else: pass init_fielddtypes[k] = v.annotations return ElementView(init_fieldvalues, init_fielddtypes)
```

```
@classmethod def get_model_spec_cls(cls, memo: dict[str, Any]) -> ElementView: # memo[self.name] = {} init_fieldvalues = {} init_fielddtypes = {} for k, v in cls.lam_schema.items(): if isinstance(v, LAMField_Element): memo[k] = {} init_fieldvalues[k] = v.value.get_model_spec(k, memo[k]) # clone = v.clone_unfrozen().value elif isinstance(v, LAMField): clone = deepcopy(v.value) init_fieldvalues[k] = clone else: pass init_fielddtypes[k] = v.annotations return ElementViewCls(init_fieldvalues, init_fielddtypes, cls.name, cls.modules)
```

`__lam_schema__` class-attribute instance-attribute

```
__lam_schema__ = {}
```

`frozen` property

```
frozen: bool
```

`frozen_cls` classmethod property

```
frozen_cls: bool
```

`mutable_obj` classmethod property

```
mutable_obj: bool
```

Functions

`__setattr__`

```
__setattr__(key: str, value: Any) -> None
```

`clone_as_mutable_variant`

```
clone_as_mutable_variant(*, deep: bool = True, _memo: Dict[int, Self] | None = None) -> Self
```

`freeze`

```
freeze(force: bool = False) -> None
```

`freeze_class` classmethod

```
freeze_class(force: bool = False) -> None
```

`validate_schema`

```
validate_schema() -> None
```

`validate_schema_class` classmethod

```
validate_schema_class() -> None
```

Functions

3.1.4 Defines

Attributes

`ALLOWED_ANNOTATIONS` module-attribute

```
ALLOWED_ANNOTATIONS: dict[str, Any] = {'Union': Union, 'Optional': Optional, 'List': List, 'Dict': Dict, 'Tuple': Tuple, 'Set': Set, 'FrozenSet': FrozenSet, 'Annotated': Annotated, 'int': int, 'str': str, 'float': float, 'bool': bool, 'complex': complex, 'bytes': bytes, 'None': type(None), 'list': list, 'dict': dict, 'set': set, 'frozenset': frozenset, 'tuple': tuple}
```

`ALLOWED_HELPERS_DEFAULT` module-attribute

```
ALLOWED_HELPERS_DEFAULT: dict[str, object] = {'math': ALLOWED_HELPERS_MATH, 'print': print, 'abs': abs, 'round': round, 'min': min, 'max': max, 'sum': sum, 'len': len, 'sorted': sorted, 'tuple': tuple, 'list': list, 'dict': dict, 'set': set, 'int': int, 'float': float, 'str': str, 'bool': bool, 'bytes': bytes, 'complex': complex, 'range': range}
```

`ALLOWED_HELPERS_MATH` module-attribute

```
ALLOWED_HELPERS_MATH = SimpleNamespace(sqrt=sqrt, floor=floor, ceil=ceil, trunc=trunc, fabs=fabs, copysign=copysign, hypot=hypot, exp=exp, log=log, log10=log10, sin=sin, cos=cos, tan=tan, atan2=atan2, radians=radians, degrees=degrees)
```

`ALLOWED_MODEL_FIELDS_TYPES` module-attribute

```
ALLOWED_MODEL_FIELDS_TYPES: set[type[Any], ...] = {str, int, float, complex, bool, bytes}
```

`JSONPrimitive` module-attribute

```
JSONPrimitive = Union[str, int, float, bool, None]
```

`JSONType` module-attribute

```
JSONType = Union[JSONPrimitive, List[Any], Dict[str, Any]]
```

3.1.5 Element

Classes

Element

Bases: [IElement](#)

Element class Base class to apply metaclass and set common Fields.

3.1.6 Exception

Classes

BrokenInheritance

Bases: [DABModelException](#)

BrokenInheritance Exception class inheritance chain is broken

ClosureForbidden

Bases: [FunctionForbidden](#)

ClosureForbidden Exception class

DABModelException

Bases: Exception

DABModelException Exception class Base Exception for DABModelException class

ExternalCodeForbidden

Bases: [FunctionForbidden](#)

ExternalCodeForbidden Exception class

FeatureAlreadyBound

Bases: [DABModelException](#)

FeatureAlreadyBound Exception class Feature can only be bind once

FeatureBoundToIncompatibleAppliance

Bases: [DABModelException](#)

FeatureBoundToWrongAppliance Exception class Feature have to be bound to correct appliance

FeatureBoundToNonAppliance

Bases: [DABModelException](#)

FeatureBoundToNonAppliance Exception class Feature can only be bind to Appliance class

FeatureNotBound

Bases: [DABModelException](#)

FeatureNotBound Exception class a Feature must be bound to the appliance (or parent)

FeatureWrongBound

Bases: [DABModelException](#)

FeatureWrongBound Exception class Feature can be bind to one and only one Appliance

FunctionForbidden

Bases: [DABModelException](#)

FunctionForbidden Exception class

ImportForbidden

Bases: [DABModelException](#)

ImportForbidden Exception class Imports are forbidden

IncompletelyAnnotatedField

Bases: [InvalidFieldAnnotation](#)

IncompletelyAnnotatedField Exception class The field annotation is incomplete

InvalidFeatureInheritance

Bases: [DABModelException](#)

InvalidFeatureInheritance Exception class Features of same name in child appliance need to be from same type

InvalidFieldAnnotation

Bases: [AttributeError](#), [DABModelException](#)

InvalidFieldAnnotation Exception class The field annotation is invalid

InvalidFieldName

Bases: [AttributeError](#), [DABModelException](#)

InvalidFieldName Exception class The Field name is invalid

InvalidFieldValue

Bases: [SchemaViolation](#)

InvalidFieldValue Exception class The Field value is invalid

InvalidInitializerType

Bases: [DABModelException](#)

InvalidInitializerType Exception class The initializer is not a valid type

MultipleInheritanceForbidden

Bases: [DABModelException](#)

MultipleInheritanceForbidden Exception class Multiple inheritance is forbidden when using dabmodel

NonExistingField

Bases: [SchemaViolation](#)

NonExistingField Exception class The given Field is non existing

NotAnnotatedField

Bases: [InvalidFieldAnnotation](#)

NotAnnotatedField Exception class The Field is not Annotated

ReadOnlyField

Bases: [AttributeError](#), [DABModelException](#)

ReadOnlyField Exception class The used Field is ReadOnly

ReadOnlyFieldAnnotation

Bases: [AttributeError](#), [DABModelException](#)

ReadOnlyFieldAnnotation Exception class Field annotation cannot be modified

ReservedFieldName

Bases: [AttributeError](#), [DABModelException](#)

ReservedFieldName Exception class Base Exception for DABModelException class

SchemaViolation

Bases: [AttributeError](#), [DABModelException](#)

SchemaViolation Exception class The Element Schema is not respected

UnsupportedFieldType

Bases: [InvalidFieldAnnotation](#)

UnsupportedFieldType Exception class The field type is unsupported

WrongUsage

Bases: [DABModelException](#), [RuntimeError](#)

3.1.7 Feature

Classes

Feature

Bases: [IFeature](#)

Feature class Base class for Appliance's Features. Features are optional traits of an appliance.

Attributes

Enabled class-attribute instance-attribute

```
Enabled: bool = False
```

__lam_bound_appliance__ class-attribute instance-attribute

```
__lam_bound_appliance__ = None
```

Functions

bind_appliance classmethod

```
bind_appliance(appliance_cls)
```

check_appliance_bound classmethod

```
check_appliance_bound()
```

check_appliance_compatibility classmethod

```
check_appliance_compatibility(appliance_cls)
```

3.1.8 Interfaces

Attributes

`TV_Freezable` module-attribute

```
TV_Freezable = TypeVar('TV_Freezable')
```

Classes

`FreezableElement`

Bases: `Protocol`, `Generic[TV_Freezable]`

Attributes

`frozen` property

```
frozen: bool
```

`frozen_cls` classmethod property

```
frozen_cls: bool
```

`mutable_obj` classmethod property

```
mutable_obj: bool
```

Functions

`clone_as_mutable_variant`

```
clone_as_mutable_variant(*, deep: bool = True, _memo: Dict[int, Self] | None = None) -> Self
```

`freeze`

```
freeze(force: bool = False) -> None
```

`freeze_class` classmethod

```
freeze_class(force: bool = False) -> None
```

`validate_schema`

```
validate_schema() -> None
```

`validate_schema_class` classmethod

```
validate_schema_class() -> None
```

3.1.9 Tools

library's internal tools

Attributes

Classes

AnnotationTrigger

Functions

end_trigger

```
end_trigger(ctx: Optional[AnnotationWalkerCtx]) -> None
```

init_trigger

```
init_trigger() -> None
```

process_allowed

```
process_allowed(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_annotated

```
process_annotated(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_dict

```
process_dict(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_exit

```
process_exit(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_list

```
process_list(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_set

```
process_set(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_tuple

```
process_tuple(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_union

```
process_union(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_unknown

```
process_unknown(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

AnnotationWalker

```
AnnotationWalker(ann: Any, triggers: tuple[AnnotationTrigger, ...], **kwargs)
```

Attributes

DEFAULT_ALLOWED_ANNOTATIONS class-attribute instance-attribute

```
DEFAULT_ALLOWED_ANNOTATIONS: dict[str, Any] = frozendict({'Union': Union, 'Optional': Optional, 'List': List, 'Dict': Dict, 'Tuple': Tuple, 'Set': Set, 'Annotated': Annotated, 'int': int, 'str': str, 'float': float, 'bool': bool, 'complex': complex, 'bytes': bytes, 'None': type(None), 'list': list, 'dict': dict, 'set': set, 'tuple': tuple})
```

DEFAULT_ALLOWED_TYPES class-attribute instance-attribute

```
DEFAULT_ALLOWED_TYPES = frozenset({str, int, float, complex, bool, bytes, NoneType})
```

__ann instance-attribute

```
__ann = ann
```

Functions

run

```
run() -> TriggerResult
```

AnnotationWalkerCtx

```
AnnotationWalkerCtx(origin: Any, args: Any, layer: int, parent: Optional[Self] = None, allowed_types: set[type, ...] = frozenset(), allowed_annotations: dict[str, Any] = {})
```

Attributes

__allowed_annotations instance-attribute

```
__allowed_annotations: dict[str, Any] = allowed_annotations
```

__allowed_types instance-attribute

```
__allowed_types: set[type, ...] = allowed_types
```

__arg_index instance-attribute

```
__arg_index: int | None = None
```

__edge_role instance-attribute

```
__edge_role: str | None = None
```

__edge_token instance-attribute

```
__edge_token: Any | None = None
```

__ext instance-attribute

```
__ext: dict[Any, ChainMap] = {}
```

__layer instance-attribute

```
__layer = layer
```

__origin instance-attribute

```
__origin = origin
```

__parent instance-attribute

```
__parent = parent
```

allowed_annotations property

```
allowed_annotations: Mapping[str, Any]
```

allowed_types property

```
allowed_types: FrozenSet[type]
```

arg_index property

```
arg_index: int | None
```

args instance-attribute

```
args = args
```

edge_role property

```
edge_role: str | None
```

edge_token property

```
edge_token: Any | None
```

layer property

```
layer: int
```

origin property

```
origin: Any
```

parent property

```
parent: Self
```

Functions

ns

```
ns(owner: Any) -> ChainMap
```

A per-trigger overlay namespace that inherits from parent ctx. Use as: `bag = ctx.ns(self); bag['whatever'] = ...` Lookups fall back to parent's bag automatically.

DataValidation

```
DataValidation(value: Any)
```

Bases: [AnnotationTrigger](#)

Functions

end_trigger

```
end_trigger(ctx: AnnotationWalkerCtx)
```

init_trigger

```
init_trigger() -> None
```

process_allowed

```
process_allowed(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_annotated

```
process_annotated(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_dict

```
process_dict(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_exit

```
process_exit(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_list

```
process_list(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_set

```
process_set(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_tuple

```
process_tuple(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_union

```
process_union(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_unknown

```
process_unknown(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

HorizontalValidationTrigger

```
HorizontalValidationTrigger(value: Any, *, strict_bool: bool = False, collect_all: bool = True, union_summary_max_per_branch: int = 3, show_branch_types: bool = True)
```

Bases: [AnnotationTrigger](#)

Functions

end_trigger

```
end_trigger(ctx: Optional[AnnotationWalkerCtx])
```

process_allowed

```
process_allowed(ctx: AnnotationWalkerCtx)
```

process_annotated

```
process_annotated(ctx: AnnotationWalkerCtx)
```

process_dict

```
process_dict(ctx: AnnotationWalkerCtx)
```

process_exit

```
process_exit(ctx: AnnotationWalkerCtx)
```

process_list

```
process_list(ctx: AnnotationWalkerCtx)
```

process_set

```
process_set(ctx: AnnotationWalkerCtx)
```

process_tuple

```
process_tuple(ctx: AnnotationWalkerCtx)
```

process_union

```
process_union(ctx: AnnotationWalkerCtx)
```

LAMJSONEncoder

Bases: [JSONEncoder](#)

allows to JSON encode non supported data type

Functions

default

```
default(o)
```

LAMSchemaValidation

Bases: [AnnotationTrigger](#)

Functions

end_trigger

```
end_trigger(ctx: AnnotationWalkerCtx)
```

init_trigger

```
init_trigger() -> None
```

process_allowed

```
process_allowed(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_annotated

```
process_annotated(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_dict

```
process_dict(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_exit

```
process_exit(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_list

```
process_list(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_set

```
process_set(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_tuple

```
process_tuple(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

process_union

```
process_union(ctx: AnnotationWalkerCtx) -> None | TriggerResult
```

SchemaValidationError

```
SchemaValidationError(path: tuple[Any, ...], msg: str)
```

Bases: [TypeError](#)

Attributes

path instance-attribute

```
path = path
```

Functions

TriggerResult *dataclass*

```
TriggerResult(replace_with: Any | None = None, skip_children: bool = False, restart_with: Any | None = None)
```

Attributes**replace_with** class-attribute instance-attribute`replace_with: Any | None = None`**restart_with** class-attribute instance-attribute`restart_with: Any | None = None`**skip_children** class-attribute instance-attribute`skip_children: bool = False`**Functions****passthrough** staticmethod`passthrough() -> Self`**replace** staticmethod`replace(value: Any) -> Self`**restart** staticmethod`restart(value: Any) -> Self`**skip** staticmethod`skip() -> Self`**Functions**

LAMdeepfreeze

`LAMdeepfreeze(value)`

recursive freeze helper function

is_data_attribute

`is_data_attribute(name: str, value: any) -> bool`

3.1.10 Lam field

Constraint

ATTRIBUTES

T_Field module-attribute

```
T_Field = TypeVar('T_Field')
```

CLASSES

Constraint

```
Constraint()
```

Bases: `Generic[T_Field]`

Constraint class Base class for Field's constraints

Functions

check

```
check(value: T_Field) -> bool
```

Check if a Constraint is completed

Lam field

ATTRIBUTES

TV_LABField module-attribute

```
TV_LABField = TypeVar('TV_LABField')
```

CLASSES

LAMField

```
LAMField(name: str, val: Optional[TV_LABField], ann: Any, i: LAMFieldInfo)
```

Bases: `Generic[TV_LABField]`

This class describe a Field in Schema

Attributes

`__annotations` instance-attribute

```
__annotations: Any
```

`__frozen` instance-attribute

```
__frozen: bool = False
```

`__frozen_value_set` instance-attribute

```
__frozen_value_set: True = False
```

`__info` instance-attribute

```
__info: LAMFieldInfo = deepcopy(i)
```

`__name` instance-attribute

```
__name: str = name
```

`__source` instance-attribute

```
__source: Optional[type] = None
```

`annotations` property

```
annotations: Any
```

Returns Field's annotation

`constraints` property

```
constraints: list[Constraint]
```

Returns Field's constraint

`default_value` property

```
default_value: Any
```

Returns Field's default value (frozen)

`doc` property

```
doc: str
```

Returns Field's documentation

frozen_value property

```
frozen_value: Any
```

info property

```
info: LAMFieldInfo
```

Returns Field's info

name property

```
name: str
```

raw_value property

```
raw_value: Optional[TV_LABField]
```

Returns Field's value

value property

```
value: Any
```

Returns Field's value (frozen)

Functions

add_constraint

```
add_constraint(cons: Constraint) -> None
```

Adds constraint to the Field

add_source

```
add_source(src: type) -> None
```

Adds source Appliance to the Field

clone_unfrozen

```
clone_unfrozen() -> Self
```

freeze

```
freeze()
```

is_frozen

```
is_frozen() -> bool
```

update_value

```
update_value(val: Optional[TV_LABField] = None) -> None
```

Updates Field's value

validate

```
validate(val: Optional[TV_LABField])
```

validate_self

```
validate_self()
```

LAMFieldFactory

Functions

`create_field` staticmethod

```
create_field(name: str, val: Optional[TV_LABField], anno: Any, info: LAMFieldInfo) -> LAMField
```

`LAMField_Element`

```
LAMField_Element(name: str, val: Optional[TV_LABField], ann: Any, i: LAMFieldInfo)
```

Bases: `LAMField[FreezableElement]`

Attributes

`default_value` property

```
default_value: Any
```

Functions

`update_value`

```
update_value(val: Optional[FreezableElement] = None) -> None
```

`validate`

```
validate(val: Optional[FreezableElement])
```

FUNCTIONS

Lam field info

CLASSES

LAMFieldInfo

```
LAMFieldInfo(*, doc: str = '', constraints: Optional[List[Constraint]] = None)
```

This Class allows to describe a Field in Appliance class

Attributes

`__constraints` instance-attribute

```
__constraints: list[Constraint]
```

`__doc` instance-attribute

```
__doc: str = doc
```

`constraints` property

```
constraints: list[Constraint[Any]]
```

Returns Field's constraints

`doc` property

```
doc: str
```

Returns Field's documentation

Functions

`add_constraint`

```
add_constraint(constraint: Constraint)
```

3.1.11 Meta

Appliance

CLASSES

FUNCTIONS

Element

ATTRIBUTES

T_BE module-attribute

```
T_BE = TypeVar('T_BE', bound='BaseElement')
```

T_Meta module-attribute

```
T_Meta = TypeVar('T_Meta', bound='_MetaElement')
```

CLASSES

ClassMutable

Bases: [ElementOptions](#)

ElementOptions

IAppliance

Bases: [IBaseElement](#)

IBaseElement

Bases: [BaseElement](#)

Functions

clone_as_mutable_variant

```
clone_as_mutable_variant(*, deep: bool = True, _memo: Dict[int, BaseElement] | None = None) -> BaseElement
```

IElement

Bases: [IBaseElement](#)

IFeature

Bases: [IBaseElement](#)

IMutableVariant

ModelSpecView

```
ModelSpecView(values: dict[str, Any], types_map: dict[str, type], name: str, module: str)
```

ModelSpecView class A class that will act as fake BaseElement proxy to allow setting values

Attributes

`__module__` property writable

```
__module__: str
```

returns proxified module's name

`__name__` property

```
__name__: str
```

returns proxified class' name

`__slots__` class-attribute instance-attribute

```
__slots__ = ('_vals', '_types', '_touched', '_name', '_module')
```

Functions

`__getattr__`

```
__getattr__(name: str) -> Any
```

internal proxy getattr

```
__setattr__
```

```
__setattr__(name: str, value: Any)
```

internal proxy setattr

export

```
export() -> dict
```

exports all proxified values

ObjectMutable

Bases: [ElementOptions](#)

FUNCTIONS

get_mutable_variant

```
get_mutable_variant(base: Type[BaseElement]) -> Type[BaseElement]
```

Return a subclass of `base` that behaves the same except that instances are created object-mutable (because the class was defined with `options=(ObjectMutable,)`).

Feature